



Introducing the FireHalt® range of ceiling lighting fire protection.
Downlighter and Recessed Luminaire Covers

Intumescent Downlighter Covers

FireHalt® Downlighter covers have been developed to provide maximum protection for holes created by the introduction of a downlighter and to allow for ease of fitting. In a fire situation, the cover expands internally to fill all the available space with a fire resistant, highly insulating char.



After Fire (cut away section)



Before Fire (cut away section)

Key Features

- Cover is Flexible and Lightweight and can be fitted from below or above the ceiling.
- Cover is ventilated to reduce heat build up in the light fitting.
- Simple fixing method; can be fitted in seconds.
- No screws, drilling or support required.
- Can be used in suspended plasterboard and concrete ceilings.
- Cost effective
- Covers a wide range of mains and low voltage downlighters.
- For thirty and 60 minute fire rated ceilings.
- Prevents fire from penetrating the ceiling void and retains ceiling's fire protection integrity.
- When exposed to fire it provides a highly insulating, stable char.
- Unaffected by moisture, and none toxic.
- Once it is installed it is free from additional maintenance.
- Once fitted, downlighter can be installed as normal

Recessed Luminaire Covers

FireHalt® Luminaire covers have been developed to provide maximum protection for ceilings where fire resistant tiles have been replaced by light fittings. These covers have been designed to allow for ease of fitting. The covers incorporate ventilation slots to reduce any potential build up of heat in the light



- ✓ **Maintains the fire protection performance of the ceiling and prevents fire from penetrating the ceiling void**
- ✓ **No Clips, screws, drilling or additional support required**
- ✓ **Supplied as a flat pack. Simple to fix in minimal time (under 60 seconds). No special training required.**
- ✓ **Sizes to fit a wide range of modular fittings up to 1200 x 600 mm**
- ✓ **Cost effective**

Sizes Available		
O/D	Height	Cut-out Size
150	150	50 to 75
200	200	75 to 100
250	250	100 to 140

For further details please contact:

MR BRENDAN McCORMACK, Marketing Director
Saveguard (UK) Ltd
Tame Valley Mill Dukinfield Cheshire SK16 5NB
Telephone: 44 (0)161 308 5500
Facsimile : 44 (0)161 344 2486

Be safe, be sure, Fit

FireHalt® Flexible Fire Barriers

